according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Biresin® lineTEC® EP 100 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Tooling system

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Deutschland GmbH

Kornwestheimer Str. 103-107

D-70439 Stuttgart

Telephone : +49 711 8009 0 E-mail address of person : EHS@de.sika.com

responsible for the SDS

1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number):

GBK GmbH Global Regulatory Compliance +49(0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1 H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

rget organ toxicity - single ex- H335: May cause respiratory irritation.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B



Revision Date 04.05.2018 Version 1.0 Print Date 04.05.2018

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : **Prevention**:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Im-

mediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/doctor.

Hazardous components which must be listed on the label:

9046-10-0 Polyoxypropylenediamine239-556-6 2-methylpentane-1,5-diamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	Classification	Concentration
CAS-No.	(REGULATION (EC)	[%]
EC-No.	No 1272/2008)	
Registration number		
Polyoxypropylenediamine	Skin Corr.1C; H314	>= 40 - < 60
9046-10-0	Eye Dam.1; H318	
618-561-0	Aquatic Chronic3;	
01-2119557899-12-XXXX	H412	
2-methylpentane-1,5-diamine	Acute Tox.4; H302	>= 25 - < 40
15520-10-2	Acute Tox.4; H332	
239-556-6	Acute Tox.4; H312	
	Skin Corr.1A; H314	
	Eye Dam.1; H318	
	STOT SE3; H335	
	,	

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B



Revision Date 04.05.2018 Version 1.0 Print Date 04.05.2018

Reaction product of 2,4-Dinitrotoluene and 2,6-Dinitrotoluene and hydrogen	Acute Tox.4; H302 Skin Corr.1B; H314 Eye Dam.1; H318	>= 25 - < 40
939-489-9		
01-2119977080-39-XXXX		
Contains:		
4-methylcyclohexane-1,3-diamine		
2-methylcyclohexane-1.3-diamine		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Health injuries may be delayed.

corrosive effects irritant effects

Causes serious eye damage.

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B



May cause respiratory irritation.

Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B





SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the

given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures

when handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Storage class (TRGS 510) : 8A, Combustible, corrosive hazardous materials

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

Revision Date 04.05.2018

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B



proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light brown

Odour : amine-like

Odour Threshold : No data available

Flash point : > 101 °C

Autoignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Explosive properties : No data available

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B

Revision Date 04.05.2018 Version 1.0

Oxidizing properties : No data available

: ca. 12,2

at 20 °C

Melting point/range / Freez-

ing point

Boiling point/boiling range

: No data available

: No data available

Vapour pressure : 0,29 hPa

Density : ca.0,92 g/cm3

at 20 °C

Water solubility : insoluble

Partition coefficient: n-

octanol/water Viscosity, dynamic : No data available

: 10 mPa.s at 20 °C

Viscosity, kinematic : < 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

: No data available Evaporation rate

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Country DE 100000020883

7 / 12

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B

Revision Date 04.05.2018 Version 1.0



No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

2-methylpentane-1,5-diamine:

Acute oral toxicity : LD50 Oral (Rat): 1.170 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.870 mg/kg

Reaction product of 2,4-Dinitrotoluene and 2,6-Dinitrotoluene and hydrogen:

Acute oral toxicity : LD50 Oral (Rat): ca. 1.276 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Polyoxypropylenediamine:

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B

Revision Date 04.05.2018 Version 1.0 Print Date 04.05.2018

Toxicity to algae : EC50: 15 mg/l, 72 h, Pseudokirchneriella subcapitata (algae)

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

Toxicity to daphnia and other : EC50: 80 mg/l, 48 h, Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classifica-

tion of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular

waste identification number.

Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor. Sika has agreed disposal contracts for all packaging which is

brought into circulation in Germany. For further details see www.sika.de

SECTION 14: Transport information

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B

Revision Date 04.05.2018 Version 1.0 Print Date 04.05.2018

Sika ®

ADR

14.1 UN number : 2735

14.2 UN proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.

(Polyoxypropylenediamine, 2-methylpentane-1,5-diamine)

14.3 Transport hazard : 8

class(es)

14.4 Packing group: IIClassification Code: C7Labels: 8Tunnel restriction code: (E)14.5 Environmental hazards: no

IATA

14.1 UN number : 2735

14.2 UN proper shipping name : Amines, liquid, corrosive, n.o.s.

(Polyoxypropylenediamine, 2-methylpentane-1,5-diamine)

14.3 Transport hazard : 8

class(es)

14.4 Packing group: IILabels: 814.5 Environmental hazards: no

IMDG

14.1 UN number : 2735

14.2 UN proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.

(Polyoxypropylenediamine, 2-methylpentane-1,5-diamine)

14.3 Class : 8

14.4 Packing group: IILabels: 8EmS Number 1: F-AEmS Number 2: S-B14.5 Marine pollutant: no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

(3)

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B



REACH Information: All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water contaminating class

(Germany)

: WGK 2 significantly water endangering

AwSV

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : 25 %

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 Harmful if swallowed. H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic
Eye Dam.
Skin Corr.
Chronic aquatic toxicity
Serious eye damage
Skin corrosion

STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route Chemical Abstracts Service Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

Country DE 100000020883

CAS

DNEL

11 / 12

Revision Date 04.05.2018

MARPOL

according to Regulation (EC) No. 1907/2006

Biresin® lineTEC® EP 100 Part B



International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

Version 1.0

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

Classification of the mixture: Classification procedure:

Skin Corr. 1 H314 Based on product data or assessment
Eye Dam. 1 H318 Based on product data or assessment
STOT SE 3 H335 Calculation method

Aquatic Chronic 3 H335 Calculation method

Aquatic Chronic 3 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!