

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Biresin® lineTEC® EP 180 Part A**



Revision Date 13.03.2020

Version 4.0

Print Date 13.03.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name : Biresin® lineTEC® EP 180 Part A

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Product use : Tooling system

**1.3 Details of the supplier of the safety data sheet**

Company name of supplier : Sika Deutschland GmbH  
Kornwestheimer Str. 103-107  
D-70439 Stuttgart  
Telephone : +49 711 8009 0  
E-mail address of person : EHS@de.sika.com  
responsible for the SDS

**1.4 Emergency telephone number**

Emergency CONTACT (24-Hour-Number):  
GBK GmbH Global Regulatory Compliance +49(0)6132-84463

**SECTION 2: Hazards identification**



**2.1 Classification of the substance or mixture**

**Classification (REGULATION (EC) No 1272/2008)**

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

**2.2 Label elements**

**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H411	Toxic to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b>	
		P261	Avoid breathing dust/ fume/ gas/ mist/ va-

**SAFETY DATA SHEET**  
 according to Regulation (EC) No. 1907/2006  
**Biresin® lineTEC® EP 180 Part A**



Revision Date 13.03.2020

Version 4.0

Print Date 13.03.2020

		pours/ spray.
P264		Wash skin thoroughly after handling.
P273		Avoid release to the environment.
P280		Wear protective gloves/ eye protection/ face protection.
<b>Response:</b>		
P333 + P313		If skin irritation or rash occurs: Get medical advice/ attention.
P391		Collect spillage.

Hazardous components which must be listed on the label:

- reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
- reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
- oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Components**

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6 500-033-5 01-2119456619-26-XXXX	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 60 - < 80
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	9003-36-5 500-006-8 01-2119454392-40-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 10 - < 20
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 10 - < 20



---

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
Excessive lachrymation  
Erythema  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
sensitising effects
- Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.



### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should



- not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Storage class (TRGS 510) : 10, Combustible liquids
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Biresin® lineTEC® EP 180 Part A**



Revision Date 13.03.2020

Version 4.0

Print Date 13.03.2020

and protective boots are additionally recommended for mixing and stirring work.  
Respiratory protection : No special measures required.

**Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

Appearance : liquid  
Colour : colourless  
Odour : characteristic  
Odour Threshold : No data available  
  
pH : Not applicable  
  
Melting point/range / Freezing point : No data available  
Boiling point/boiling range : No data available  
  
Flash point : > 101 °C  
Method: closed cup  
  
Evaporation rate : No data available  
  
Flammability (solid, gas) : No data available  
  
Upper explosion limit / Upper flammability limit : No data available  
  
Lower explosion limit / Lower flammability limit : No data available  
  
Vapour pressure : 0,01 hPa  
  
Relative vapour density : No data available  
  
Density : ca. 1,12 g/cm<sup>3</sup> (20 °C)  
  
Solubility(ies)  
Water solubility : No data available  
  
Solubility in other solvents : No data available  
  
Partition coefficient: n-octanol/water : No data available  
Auto-ignition temperature : No data available  
  
Decomposition temperature : No data available

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Biresin® lineTEC® EP 180 Part A**



Revision Date 13.03.2020

Version 4.0

Print Date 13.03.2020

Viscosity	
Viscosity, dynamic	: ca. 1.150 mPa.s (20 °C)
Viscosity, kinematic	: > 20,5 mm <sup>2</sup> /s (40 °C)
Explosive properties	: No data available
Oxidizing properties	: No data available

## 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

|| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

|| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Biresin® lineTEC® EP 180 Part A**



Revision Date 13.03.2020

Version 4.0

Print Date 13.03.2020

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

**Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Components:**

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l  
aquatic invertebrates Exposure time: 48 h

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available





#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular waste identification number.  
Completely emptied packagings may be given for recycling.  
Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.  
Sika has agreed disposal contracts for all packaging which is brought into circulation in Germany.  
For further details see [www.sika.de](http://www.sika.de)

---

### SECTION 14: Transport information

#### 14.1 UN number

**ADR** : UN 3082  
**IMDG** : UN 3082  
**IATA** : UN 3082

#### 14.2 UN proper shipping name

**ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(epoxy resin)  
**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(epoxy resin)

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**Biresin® lineTEC® EP 180 Part A**



Revision Date 13.03.2020

Version 4.0

Print Date 13.03.2020

**IATA** : Environmentally hazardous substance, liquid, n.o.s.  
(epoxy resin)

**14.3 Transport hazard class(es)**

**ADR** : 9

**IMDG** : 9

**IATA** : 9

**14.4 Packing group**

**ADR**

Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Tunnel restriction code : (-)

**IMDG**

Packing group : III  
Labels : 9  
EmS Code : F-A, S-F

**IATA (Cargo)**

Packing instruction (cargo aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous

**IATA (Passenger)**

Packing instruction (passenger aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous

**14.5 Environmental hazards**

**ADR**

Environmentally hazardous : yes

**IMDG**

Marine pollutant : yes

**IATA (Passenger)**

Environmentally hazardous : yes

**IATA (Cargo)**

Environmentally hazardous : yes

**14.6 Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable for product as supplied.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Water contaminating class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

|| Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 0,19 %  
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0,19 %

GISCODE : RE30

**Other regulations:**

Product is no subject to the Chemicals Prohibition Ordinance.



## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

## SECTION 16: Other information

### Full text of H-Statements

H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H411	:	Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

#### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Biresin® lineTEC® EP 180 Part A**



Revision Date 13.03.2020

Version 4.0

Print Date 13.03.2020

---

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

DE / EN