

THE SOLUTION FOR DEFECTIVE PIPES



Table of Contents	Notes	Page(s)
House-Connection & InHouse - Liners		2
House Connection - Liners		3-4
UV-Curing		4-5
House-Connection - Resin Systems		5-6
Main Sewer Pipe - Liners		7
Main Sewer Pipe - Resin Systems		8
Partial Pipe Rehabilitation		9
Connection Branch Rehabilitation		10
Partial Pipe Rehabilitation - WILLKAT Resin Systems		11
Utilities - Calibration Hoses		12-13
Utilities - Preliners & Support Caps		13-14
Terms of Payment & Delivery; Contact Info		16

House Connection & InHouse - Liners

lineTEC Flex; $\overline{r} \leq 90^\circ, \leq 3D$

3,5 mm KnitTex + PU-Coating

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
349313	lineTEC Flex 3D	DN 50-70	6,50 cm	50 / 100	3,5 mm	2,8 mm	x	on request	
352239	lineTEC Flex 3D	DN 60-80	8,00 cm	50 / 100	3,5 mm	2,8 mm		on request	
349315	lineTEC Flex 3D	DN 70-100	9,25 cm	50 / 100	3,5 mm	2,8 mm	x	on request	
351849	lineTEC Flex 3D	DN 80-100	11,00 cm	50 / 100	3,5 mm	2,8 mm		on request	
349316	lineTEC Flex 3D	DN 100-150	12,75 cm	50 / 100	3,5 mm	2,8 mm	x	on request	
349317	lineTEC Flex 3D	DN 125-150	15,50 cm	50 / 100	3,5 mm	2,8 mm		on request	
349319	lineTEC Flex 3D	DN 150-200	19,50 cm	50 / 100	3,5 mm	2,8 mm	x	on request	
349320	lineTEC Flex 3D	DN 200-250	25,50 cm	50 / 100	3,5 mm	2,8 mm		on request	

lineTEC ProFlex, $\overline{r} \leq 90^\circ, \leq 3D$

4,5 mm HighTex + PU-Coating // 90° Bends // 3D

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
161854	lineTEC ProFlex 3D	DN 50-70	5,75 cm	50 / 100	4,5 mm	3,8 mm		on request	
351691	lineTEC ProFlex	DN 70-80	9,00 cm	50 / 100	4,5 mm	3,8 mm		on request	
159588	lineTEC ProFlex 3D	DN 70-100	9,00 cm	50 / 100	4,5 mm	3,8 mm	x	on request	
157230	lineTEC ProFlex	DN 80-100	9,50 cm	50 / 100	4,5 mm	3,8 mm		on request	
351692	lineTEC ProFlex	DN 100-125	12,00 cm	50 / 100	4,5 mm	3,8 mm		on request	
157231	lineTEC ProFlex 3D	DN 100-150	13,00 cm	50 / 100	4,5 mm	3,8 mm	x	on request	
157232	lineTEC ProFlex	DN 125-150	15,00 cm	50 / 100	4,5 mm	3,8 mm		on request	
157233	lineTEC ProFlex 3D	DN 150-200	19,50 cm	50 / 100	4,5 mm	3,8 mm	x	on request	
157234	lineTEC ProFlex	DN 200-250	25,00 cm	50 / 100	4,5 mm	3,8 mm	x	on request	
168069	lineTEC ProFlex	DN 250-300	33,50 cm	50 / 100	4,5 mm	3,8 mm		on request	

WT = Wall Thickness (without resin)

FWT = Final Wall Thickness (estimated) after curing

The information regarding the final wall thickness (FWT) requires installation according to the installation manual. Please note the data sheets of the respective products, see www.linetec.info/downloads.

House Connection - Liners**lineTEC ProFlex XT; $\beta \leq 90^\circ$, $\leq 3D$** **6 mm Hightex + PU-Coating // 90° Bends // 3D**

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
341667	lineTEC ProFlex XT 3D	DN 150-200	20,00 cm	50 / 100	6 mm	4,8 mm	x	on request	
341668	lineTEC ProFlex XT	DN 200-250	25,75 cm	50 / 100	6 mm	4,8 mm	x	on request	
341672	lineTEC ProFlex XT	DN 250-300	30,75 cm	50 / 100	6 mm	4,8 mm	x	on request	

lineTEC ProFlex S; $\beta \leq 45^\circ$ **5 mm Felt-Liner with Steam-Tight PU-Coating**

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
228735	lineTEC ProFlex S	DN 100	13,00 cm	50 / 100	5 mm	4,0 mm		on request	
228736	lineTEC ProFlex S	DN 125	15,75 cm	50 / 100	5 mm	4,0 mm	x	on request	
228737	lineTEC ProFlex S	DN 150	19,75 cm	50 / 100	5 mm	4,0 mm	x	on request	
228738	lineTEC ProFlex S	DN 200	25,75 cm	50 / 100	5 mm	4,0 mm	x	on request	
327939	lineTEC ProFlex S	DN 225	30,25 cm	50 / 100	5 mm	4,0 mm		on request	
327942	lineTEC ProFlex S	DN 250	33,50 cm	50 / 100	5 mm	4,0 mm	x	on request	

lineTEC ProFlex S XT; $\beta \leq 45^\circ$ **6 mm felt-Liner with Steam-Tight PU-Coating**

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
314204	lineTEC ProFlex S XT	DN 150	20,00 cm	50 / 100	6 mm	4,5 mm	x	on request	
314205	lineTEC ProFlex S XT	DN 200	25,75 cm	50 / 100	6 mm	4,5 mm	x	on request	
327945	lineTEC ProFlex S XT	DN 225	30,75 cm	50 / 100	6 mm	4,5 mm		on request	
327946	lineTEC ProFlex S XT	DN 250	34,50 cm	50 / 100	6 mm	4,5 mm	x	on request	

lineTEC ProFlex S Soft; $\beta \leq 45^\circ$ **5 mm Felt-Liner with Steam-Tight PU-Coating**

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
349009	lineTEC ProFlex S Soft	DN 100	12,75 cm	50 / 100	5 mm	4,0 mm	x	on request	
349010	lineTEC ProFlex S Soft	DN 125	15,50 cm	50 / 100	5 mm	4,0 mm	x	on request	
349011	lineTEC ProFlex S Soft	DN 150	20,00 cm	50 / 100	5 mm	4,0 mm	x	on request	
349012	lineTEC ProFlex S Soft	DN 200	25,75 cm	50 / 100	5 mm	4,0 mm	x	on request	
350660	lineTEC ProFlex S Soft	DN 225	30,75 cm	50 / 100	5 mm	4,0 mm		on request	
351922	lineTEC ProFlex S Soft	DN 250	34,50 cm	50 / 100	5 mm	4,0 mm		on request	

UV-Curing**lineTEC ProFlex S UV 4,5; $\beta \leq 90^\circ$** **4,5mm PES UVx 10 Felt-Liner with PU-coating**

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
363452	lineTEC ProFlex S UV 4,5	DN 100	12,75 cm	50 / 100	4,5 mm	3,8 mm	x	on request	
363453	lineTEC ProFlex S UV 4,5	DN 125	15,50 cm	50 / 100	4,5 mm	3,8 mm	x	on request	
363454	lineTEC ProFlex S UV 4,5	DN 150	20,00 cm	50 / 100	4,5 mm	3,8 mm	x	on request	
363455	lineTEC ProFlex S UV 4,5	DN 200	25,75 cm	50 / 100	4,5 mm	3,8 mm	x	on request	
363456	lineTEC ProFlex S UV 4,5	DN 250	34,50 cm	50 / 100	4,5 mm	3,8 mm	x	on request	

lineTEC ProFlex S UV 5,1; $\beta \leq 90^\circ$ **5,1mm PES UVx 10 Felt-Liner with PU-coating**

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
363459	lineTEC ProFlex S UV 5,1	DN 150	20,00 cm	50 / 100	5,1 mm	4,4 mm	x	on request	
363460	lineTEC ProFlex S UV 5,1	DN 200	30,75 cm	50 / 100	5,1 mm	4,4 mm	x	on request	
363461	lineTEC ProFlex S UV 5,1	DN 250	34,50 cm	50 / 100	5,1 mm	4,4 mm	x	on request	

UV-Curing - Resin System

Willpox LC Resin System

1K UV Epoxy Resin

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 20°	Curing 55°	Curing 70°	In Stock	Price (€/kg)	Notes
363329	WILLPOX LC	20	see data sheet @ linetec.info/downloads/				x	See Appendix Resins	

House-Connection / InHouse - Resin Systems

lineTEC EP70 Resin System

2K Epoxy Resin

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 20°	Curing 55°	Curing 70°	In Stock	Price (€/kg)	Mixed Price
287132	lineTEC EP70 Resin	20	Siehe Härter	-	-	-	x	See Appendix Resins	*€/kg
287133	lineTEC EP70 Hardener	4	60 min	27 h	150 min	50 min	x		
327948	lineTEC EP70 HT Hardener - InHouse**	4	55 min	-	150 min	50 min	x		

Resin Consumption (kg/rm)

*1	Harz EP 70, Hardener 30/ 70/ 100	DN 50	DN 70	DN 80	DN 100	DN 125	DN 150	DN 200	DN 250
7	lineTEC Flex	0,48	0,69	0,80	0,92	1,11	1,39	1,80	2,20
10	lineTEC ProFlex	0,70	0,92	1,09	1,36	1,64	2,09	2,73	3,25
11	lineTEC ProFlex S/ -Soft	-	-	-	1,5	1,8	2,3	3,00	3,92
12	lineTEC ProFlex S XT/ -Soft	-	-	-	1,64	1,98	2,57	3,26	4,27

* Distance of impregnation-rolls in mm **

In InHouse-rehabilitation situations, use resin ONLY in conjunction with EP70 HT Hardener!

Processing- and curing times may vary, depending on local conditions

WILLPOX Resin System - Small Containers

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 20°	Curing 55°	Curing 70°	In Stock	Price (€/kg)	Mixed Price
362782	WILLPOX Component A	16,0							
363320	WILLPOX 20 Component B	6,4							
362783	WILLPOX 50 Component B	4,0							
363322	WILLPOX 100 Component B	4,8							
see data sheet @ linetec.info/downloads/								See Appendix Resins	

WILLPOX Resin System - Barrel

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 20°	Curing 55°	Curing 70°	In Stock	Price (€/kg)	Mixed Price
363318	WILLPOX Component A	200							
363332	WILLPOX 20 Component B	200							
363321	WILLPOX 50 Component B	190							
363323	WILLPOX 100 Component B	190							
see data sheet @ linetec.info/downloads/								See Appendix Resins	

WILLPOX Resin System- IBC

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 20°	Curing 55°	Curing 70°	In Stock	Price (€/kg)	Mixed Price
363319	WILLPOX Component A	1000							
on request	WILLPOX 20 Component B	1000							
on request	WILLPOX 50 Component B	950							
363324	WILLPOX 100 Component B	950							
see data sheet @ linetec.info/downloads/								See Appendix Resins	

Main Sewer Pipe - Liners**lineTEC SP-Liner XF; $\beta \leq 30^\circ$** **Felt-Liner with PP-Coating**

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
245583	lineTEC SP-Liner XF	DN 200	31,5 cm	-	5,5 mm	4,5 mm	x	on request	
250125	lineTEC SP-Liner XF	DN 250	38,5 cm	-	5,5 mm	4,5 mm	x	on request	
294560	lineTEC SP-Liner XF	DN 250	38,5 cm	-	7,0 mm	5,5 mm	x	on request	
250126	lineTEC SP-Liner XF	DN 300	46,5 cm	-	5,5 mm	4,5 mm	x	on request	
294561	lineTEC SP-Liner XF	DN 300	46,5 cm	-	7,0 mm	5,5 mm	x	on request	
228778	lineTEC SP-Liner XF	DN 350	54,0 cm	-	7,0 mm	5,5 mm	x	on request	
228785	lineTEC SP-Liner XF	DN 400	61,0 cm	-	7,0 mm	5,5 mm	x	on request	

lineTEC SP-Liner XS; $\beta \leq 15^\circ$ **Felt-Liner with PP-Coating**

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
228787	lineTEC SP-Liner XS	DN 400	61,0 cm	-	8,5 mm	6,5 mm	x	on request	
229135	lineTEC SP-Liner XS	DN 500	75,5 cm	-	10 mm	8,0 mm	x	on request	
230543	lineTEC SP-Liner XS	DN 600	90,5 cm	-	10 mm	8,0 mm	x	on request	

lineTEC Hybrid; $\beta \leq 15^\circ$ **Felt-Liner with PP-Coating**

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
345034	lineTEC Hybrid	DN 300	46,5 cm	-	7 mm	5,5 mm		on request	
345035	lineTEC Hybrid	DN 400	61,0 cm	-	7 mm	5,5 mm		on request	
345036	lineTEC Hybrid	DN 500	76,0 cm	-	7 mm	5,5 mm		on request	
345037	lineTEC Hybrid	DN 600	93,0 cm	-	7 mm	5,5 mm		on request	

Remarks:

The SP-Liners above are generally kept in stock and are delivered in the ordered lengths. For order-quantities shorter than 20m, we charge an additional handling fee of 20.00€. We are also happy to offer liners with customized wallthickness and/or diameters at your request. for costumization-requests, please contact us via e-mail at: lineTEC@vfg.de.

Main Sewer Pipe - Resin Systems

Resin Consumption (kg/rm)

*	Harz EP 180/ EP 500	DN 150	DN 200	DN 250	DN 300	DN 350	DN 400	DN 500	DN 600
5,5	lineTEC SP-Liner XF	2,37	3,16	3,95	4,74	5,54	6,33	7,91	9,49
7	lineTEC SP-Liner XF	2,97	3,95	4,94	5,93	6,92	7,91	9,88	11,86
8,5	lineTEC SP-Liner XS	3,56	4,74	5,93	7,12	8,3	9,49	11,86	14,23
10	lineTEC SP-Liner XS	4,15	5,54	6,92	8,3	9,69	11,07	13,84	16,61

* Wallthickness in mm

lineTEC EP180 // EP180/500 Resin System - Small Containers 2K Epoxy Resin

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 20°	Curing 55°	Curing 70°	In Stock	Price (€/kg)	Mixed Price
206796	lineTEC EP180 Resin	20	see hardener	-	-	-	x	See Appendix Resins	*€/kg
206797	lineTEC EP180 Hardener	5	140 min	-	6 h	2 h	x		
356389	lineTEC EP180/500 Hardener	8,8	-	-	-	-			

lineTEC EP180 Resin Systems - IBC

2K Epoxidharz

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 20°	Curing 55°	Curing 70°	In Stock	Price (€/kg)	Mixed Price
200489	lineTEC EP180 Resin	1000	see hardener	-	-	-		See Appendix Resins	*€/kg
200491	lineTEC EP180 Hardener	950	140 min	-	6 h	2 h			

WILLPOX 480 Resin Systems

2K Epoxidharz

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 15°	Curing 20°	Curing 25°	In Stock	Price (€/kg)	Mixed Price
siehe Seite 6	WILLPOX Component A, various Packaging Units						see page six	See Appendix Resins	*€/kg
363326	WILLPOX 480 Component B	4,5							
363327	WILLPOX 480 Component B	190,0							
363328	WILLPOX 480 Component B	950,0							

see data sheet @
linetec.info/downloads/

Partial Pipe Rehabilitation

lineTEC ProFlex uncoated; $\alpha \leq 90^\circ$

Hightex // 90° // 3D

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
345092	lineTEC ProFlex uncoated	DN 50	5,75 cm	25 / 50	4,5 mm	4,0 mm		on request	
225617	lineTEC ProFlex uncoated	DN 70-100	9,00 cm	25 / 50	4,5 mm	4,0 mm	x	on request	
210265	lineTEC ProFlex uncoated	DN 100-150	13,00 cm	25 / 50	4,5 mm	4,0 mm	x	on request	
210266	lineTEC ProFlex uncoated	DN 125-150	15,00 cm	25 / 50	4,5 mm	4,0 mm		on request	
210267	lineTEC ProFlex uncoated	DN 150-200	19,50 cm	25 / 50	4,5 mm	4,0 mm	x	on request	
210268	lineTEC ProFlex uncoated	DN 200-250	25,00 cm	25 / 50	4,5 mm	4,0 mm		on request	
355338	lineTEC ProFlex uncoated	DN 250-300	33,50 cm	25 / 50	4,5 mm	4,0 mm		on request	

lineTEC Glass-Matts

Art.-No.	Product Name	Diameter	Flat Size	Length	WT	FWT	In Stock	Price (€/rm)	Notes
333236	Advantex Glass-Complex-Fabric	50kg	1,25 m	38m	1050 g/m ²			on request	
on request	Bidirektionales Glass-Complex-Clutch	50kg	1,30 m	-	1086 g/m ²			on request	

Partial Pipe Rehabilitation - Sikotec 3P Resin System

SIKOTEC Summer- and Winter Resin System

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 15°	Curing 20°	Curing 25°	In Stock	Price (€/kg)	Mixed Price
333233	SIKOTEC - Wasserglas (A)	15,5kg						on request	
333227	SIKOTEC-3P Harz W1 (B)	24,8 kg						on request	
333229	SIKOTEC-3P Harz S1 (B)	24,8 kg						on request	
356849	SIKOTEC-3P T-Harz W01 (B)	24,8 kg						on request	

see data sheet @ linetec.info/downloads/

Connection Branch Rehabilitation

lineTEC Universal TY-Liner Flex

KnitTex 3,5mm, PU-coated, universal connection liner for T- and Y- connections

Art.-No.	Product Name	Diameter**	Flat Size	Length	WT	FWT*	In Stock	Price (€/rm)	Notes
363207	lineTEC Universal TY-Liner Flex	DN 50/150+	-	-	3,5 mm	2,5 mm	x	on request	
363208	lineTEC Universal TY-Liner Flex	DN 70/150+	-	-	3,5 mm	2,5 mm	x	on request	
363209	lineTEC Universal TY-Liner Flex	DN 100/150+	-	-	3,5 mm	2,5 mm	x	on request	
363210	lineTEC Universal TY-Liner Flex	DN 125/150+	-	-	3,5 mm	2,5 mm	x	on request	
363211	lineTEC Universal TY-Liner Flex	DN 150/150+	-	-	3,5 mm	2,5 mm	x	on request	

lineTEC Universal TY-Liner ProFlex

KnitTex 4,5mm, PU-coated, universal connection liner for T- and Y- connections

Art.-No.	Product Name	Diameter**	Flat Size	Length	WT	FWT*	In Stock	Price (€/rm)	Notes
363212	lineTEC Universal TY-Liner ProFlex	DN 100/250+	-	-	4,5 mm	3,5 mm	x	on request	
363213	lineTEC Universal TY-Liner ProFlex	DN 125/250+	-	-	4,5 mm	3,5 mm	x	on request	
363214	lineTEC Universal TY-Liner ProFlex	DN 150/250+	-	-	4,5 mm	3,5 mm	x	on request	
363215	lineTEC Universal TY-Liner ProFlex	DN 200/250+	-	-	4,5 mm	3,5 mm	x	on request	

*Final wall-thickness (FWT) 2,5mm (Flex) and 3-3,5mm (ProFlex) determined by utilized setting tool, resin system and curing method.

**Legend: DN Connection Pipe / DN Main Pipe; "+": up to this main-pipe diameter, pipe-enclosing reahabilitation is possible

Connection Branch Rehabilitation - Epoxy Resin

WILLPOX 20 Resin System - Small Container

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 20°	Curing 55°	Curing 70°	In Stock	Price (€/kg)	*€/kg Mixed Price
362782	WILLPOX Component A	16,0		see data sheet @				See Appendix Resins	
363320	WILLPOX 20 Component B	6,4		linetec.info/downloads/					

Note: lineTEC ProFlex uncoated and lineTEC Universal TY-Liner can be employed with epoxy- or silicate-resin systems! For silicate-resin systems, please see page 12!

Partial Pipe Rehabilitation - WILLKAT Resin Systems

3K Silicate Resin System for Short Liner Rehabilitation

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 15°	Curing 20°	Curing 25°	In Stock	Price (€/kg)	Mixed Price
363476	WILLKAT PL 3K Component A	28							
363479	WILLKAT PL 3K Component B	21							
363481	WILLKAT PL 3K Component C	1							
see data sheet @ linetec.info/downloads/									See Appendix Resins

2K Silicate Resin System for Short Liner Rehabilitation

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 15°	Curing 20°	Curing 25°	In Stock	Price (€/kg)	Mixed Price
363482	WILLKAT PL 2K Slow Component A	14							
363483	WILLKAT PL 2K Summer Component A	14							
363484	WILLKAT PL 2K Winter Component A	14							
363485	WILLKAT PL 2K Fast Component A	14							
363486	WILLKAT PL 2K Fast Plus Component A	14							
363487	WILLKAT PL 2K Component B	21							
see data sheet @ linetec.info/downloads/									See Appendix Resins

2K Silicate Resin System for Short Liner Rehabilitation

Art.-No.	Product Name	SKU Size(kg)	Processing 15°	Curing 15°	Curing 20°	Curing 25°	In Stock	Price (€/kg)	Mixed Price
363489	WILLKAT SL 2K Component A	13							
363491	WILLKAT SL 2K Summer Component B	10							
363493	WILLKAT SL 2K Summer Component B	20							
363494	WILLKAT SL 2K Winter Component B	10							
363495	WILLKAT SL 2K Winter Component B	20							
363496	WILLKAT SL 2K Fast Component B	10							
363497	WILLKAT SL 2K Fast Component B	20							
see data sheet @ linetec.info/downloads/									See Appendix Resins

Utilities - Calibration Hoses

lineTEC Calibration Hose Purple

PVC-coated nylon-fabric, welded, Tensile Strength: longitudinal/radial: 1300/100N/ 50mm

Art.-No.	Product Name	Diameter	Flat Size	Length	Temperature	Max. Pressure	In Stock	Price (€/rm)	Notes
327374	lineTEC Kali purple	DN 46	7,2 cm	100	50° C	< 0,5 bar	x	on request	
314247	lineTEC Kali purple	DN 63	9,8 cm	100	50° C	< 0,5 bar	x	on request	
214954	lineTEC Kali purple	DN 80	12,5 cm	100	50° C	< 0,5 bar	x	on request	
161611	lineTEC Kali purple	DN 100	16,0 cm	100	50° C	< 0,5 bar	x	on request	
161612	lineTEC Kali purple	DN 125	20,0 cm	100	50° C	< 0,5 bar	x	on request	
161613	lineTEC Kali purple	DN 150	23,5 cm	100	50° C	< 0,5 bar	x	on request	
161614	lineTEC Kali purple	DN 200	31,5 cm	100	50° C	< 0,5 bar	x	on request	

lineTEC Calibration Hose Light Blue

PVC-coated nylon-fabric, welded, Tensile Strength: longitudinal/radial: 1500/1400N/50mm

Art.-No.	Product Name	Diameter	Flat Size	Length	Temperature	Max. Pressure	In Stock	Price (€/rm)	Notes
311774	lineTEC Kali hellblau	DN 100	16,0 cm	100	50° C	< 0,5 bar	x	on request	
311775	lineTEC Kali hellblau	DN 125	20,0 cm	100	50° C	< 0,5 bar	x	on request	
311778	lineTEC Kali hellblau	DN 150	23,5 cm	100	50° C	< 0,5 bar	x	on request	
311785	lineTEC Kali hellblau	DN 200	31,5 cm	100	50° C	< 0,5 bar	x	on request	

lineTEC Calibration Hose Orange

PVC-coated nylon-fabric, sewn&welded, Tensile Strength: longitudinal/radial: 2000/1400N/50mm

Art.-No.	Product Name	Diameter	Flat Size	Length	Temperature	Max. Pressure	In Stock	Price (€/rm)	Notes
251059	lineTEC Kali orange	DN 100	16,0 cm	100	70° C	< 1,0 bar	x	on request	
251061	lineTEC Kali orange	DN 125	20,0 cm	100	70° C	< 1,0 bar	x	on request	
251063	lineTEC Kali orange	DN 150	23,5 cm	100	70° C	< 1,0 bar	x	on request	
251064	lineTEC Kali orange	DN 200	31,5 cm	100	70° C	< 1,0 bar	x	on request	
251071	lineTEC Kali orange	DN 250	39,5 cm	100	70° C	< 1,0 bar	x	on request	

lineTEC Kalibrierschlauch Grey

PVC-coated nylon-fabric, sewn&welded, Tensile Strength: 2200/2200N/50mm

Art.-No.	Product Name	Diameter	Flat Size	Length	Temperature	Max. Pressure	In Stock	Price (€/rm)	Notes
83386	lineTEC Kali grey	DN 125	19,8 cm	100	70° C	< 1,0 bar		on request	
83387	lineTEC Kali grey	DN 150	23,8 cm	100	70° C	< 1,0 bar	x	on request	
83388	lineTEC Kali grey	DN 200	31,5 cm	100	70° C	< 1,0 bar	x	on request	
120188	lineTEC Kali grey	DN 225	35,3 cm	100	70° C	< 1,0 bar		on request	
83389	lineTEC Kali grey	DN 250	39,3 cm	100	70° C	< 1,0 bar	x	on request	
83390	lineTEC Kali grey	DN 300	47,3 cm	100	70° C	< 1,0 bar	x	on request	
83391	lineTEC Kali grey	DN 350	55,0 cm	100	70° C	< 1,0 bar	x	on request	
83392	lineTEC Kali grey	DN 400	63,0 cm	100	70° C	< 1,0 bar	x	on request	
83393	lineTEC Kali grey	DN 450	70,8 cm	100	70° C	< 1,0 bar		on request	
83394	lineTEC Kali grey	DN 500	78,5 cm	100	70° C	< 1,0 bar		on request	
83395	lineTEC Kali grey	DN 600	94,3 cm	100	70° C	< 1,0 bar		on request	

Utilities - Preliner & Support Caps

lineTEC Preliner HDPE

HDPE Foil 0,1mm

Art.-No.	Product Name	Diameter	Flat Size	Length	Temperature	Max. Pressure	In Stock	Price (€/rm)	Notes
210046	lineTEC Preliner HDPE	DN 100	15,7 cm	100	80°C	-	x	on request	
210049	lineTEC Preliner HDPE	DN 150	23,5 cm	100	80°C	-	x	on request	
210054	lineTEC Preliner HDPE	DN 200	31,4 cm	100	80°C	-	x	on request	
231715	lineTEC Preliner HDPE	DN 250	39,3 cm	100	80°C	-	x	on request	
231717	lineTEC Preliner HDPE	DN 300	47,0 cm	100	80°C	-	x	on request	
231719	lineTEC Preliner HDPE	DN 350	55,0 cm	100	80°C	-	x	on request	
231720	lineTEC Preliner HDPE	DN 400	62,8 cm	100	80°C	-	x	on request	
286400	lineTEC Preliner HDPE	DN 500	78,6 cm	100	80°C	-	x	on request	

lineTEC Support Cap White

Art.-No.	Product Name	Diameter	Flat Size	Length	Temperature	Max. Pressure	In Stock	Price (€/rm)	Notes
308780	lineTEC Support Cap white	DN 100	15,7 cm	1,5	90°C	-		on request	
308781	lineTEC Support Cap white	DN 125	19,6 cm	1,5	90°C	-		on request	
308783	lineTEC Support Cap white	DN 150	23,5 cm	1,5	90°C	-		on request	
307837	lineTEC Support Cap white	DN 200	31,4 cm	1,5	90°C	-		on request	
307838	lineTEC Support Cap white	DN 250	39,3 cm	1,5	90°C	-		on request	
307843	lineTEC Support Cap white	DN 300	47,0 cm	1,5	90°C	-		on request	
308785	lineTEC Support Cap white	DN 350	55,0 cm	1,5	90°C	-		on request	
308789	lineTEC Support Cap white	DN 375	58,9 cm	1,5	90°C	-		on request	
307740	lineTEC Support Cap white	DN 400	62,8 cm	1,5	90°C	-		on request	
308769	lineTEC Support Cap white	DN 450	70,5 cm	1,5	90°C	-		on request	
308771	lineTEC Support Cap white	DN 500	78,6 cm	1,5	90°C	-		on request	
308791	lineTEC Support Cap white	DN 600	94,0 cm	1,5	90°C	-		on request	

Products on Request

Art.-No.	Product Name	Diameter	Flat Size	Length	Temperature	Max. Pressure	In Stock	Price (€/rm)	Notes
on request	lineTEC Preliner PVC	DN 100-600	-	50 / 100	70°C	< 1,0 bar		t.b.d.	
on request	lineTEC Support Cap Grey	DN 150-1200	-	1,2 m	70°C	< 1,0 bar		t.b.d.	
on request	lineTEC Support Hose White	DN 100-600	-	50 / 100	90°C	< 1,0 bar		t.b.d.	

Notes

Terms of Delivery if not agreed upon otherwise:

Time of delivery:

- Ex.-Stock approx. 2 days + shipping
- Non-stock or customized/tailor-made products
10-15 working days + shipping
- No express-delivery for dangerous goods (resins)

Terms of delivery:

- FCA Hermaringen, Incoterms 2020
- DAP Target Destination or net prod.
- Shipping cost will be charged according to actual expenditure
- Surcharge fo Dangerous Goods: 20,00 €/delivery

WE ARE HERE FOR YOU

You have questions about a rehabilitation project, would like to get information about our products or order goods?

Vereinigte Filzfabriken AG

lineTEC

Giengener Weg 66
89568 Hermaringen

Tel: +49 7322 144-333

Fax: +49 7322 144-334

E-Mail: linetec@vfg.de

Online: www.linetec.info

contact us

